

# Package: normalizeH (via r-universe)

September 16, 2024

**Version** 1.0.0

**Date** 2022-07-20

**Title** Normalize Hadamard Matrix

**Author** Baidya Nath Mandal [aut, cre]

**Maintainer** Baidya Nath Mandal <mandal.stat@gmail.com>

**Depends** R (>= 4.2.0)

**Suggests** HadamardR

**Description** Normalize a given Hadamard matrix. A Hadamard matrix is said to be normalized when its first row and first column entries are all 1, see Hedayat, A. and Wallis, W. D. (1978) ``Hadamard matrices and their applications. The Annals of Statistics, 1184-1238." <doi:10.1214/aos/1176344370>.

**License** GPL (>= 2)

**NeedsCompilation** no

**Date/Publication** 2022-07-21 12:30:02 UTC

**Repository** <https://doer0.r-universe.dev>

**RemoteUrl** <https://github.com/cran/normalizeH>

**RemoteRef** HEAD

**RemoteSha** 4e1d8e7ada83a242c992d5c0231e2cf2283406ee

## Contents

normalizeH . . . . .	2
<b>Index</b>	<b>3</b>

---

`normalizeH`*Normalized Hadamard Matrix*

---

**Description**

Converts a given Hadamard matrix to its normalized form

**Usage**

```
normalizeH(H)
```

**Arguments**

H                    A Hadamard matrix

**Value**

A normalized Hadamard matrix of same dimension as the input matrix.

**Author(s)**

Baidya Nath Mandal <mandal.stat@gmail.com>

**Examples**

```
H = matrix(c(1,1,1,-1),nrow = 2)
normalizeH(H)
```

```
require(HadamardR)
h8 <- Hadamard_Matrix(8)
normalizeH(h8)
```

# Index

\* **Hadamard matrix**

normalizeH, 2

\* **normalized**

normalizeH, 2

normalizeH, 2